

SWITCH FOR SUCCESS

SPRINT SHD





SUPER HEAVY DUTY CALCIUM SEALED TECHNOLOGY


WINNER®

SPRINT SHD

Type No		Capacity 20 hr. rate	Cranking Performance	Dimensions (mm)				Construction		Base Hold-down
		(Ah)	EN (A)	L	W	Н	T.H	Layout	Terminal	
ı	580 040 068	80	680	278	175	190	190	0	Α	В3
ī	600 044 085	100	850	353	175	190	190	0	А	В3
Ī	640 020 080	140	800	511	187	200	220	3	А	
Ī	680 032 095	180	950	513	222	200	220	3	А	
Ĺ	730 027 120	230	1200	518	273	221	241	3	А	







TECHNICAL CHARACTERISTICS

- Sealed Super Heavy Duty range with calcium expanded grid technology
- Closed type range with no maintenance during life time
- Long service life under repeated discharge-charge cycles
- Optimum capacity with EN / DIN containers

SPRINT SHD Sealed Maintenance Free series represents WINNER's innovation and contribution for reliable solutions at heavy duty vehicles with high energy demand requiring no maintenance during entire service life.

SPRINT SHD integrates a special plate group vibration resistance design for excellent performance under extreme temperature conditions, for higher discharging requirements. The special built-in-cover venting system provides anti flame protection and acid leakage prevention during vehicle tilting or high charging. It is



Wherever batteries go



VIOSY S.A. . Central Office: